

CROSSFIRE X600



x600
EPS

POWER STEERING
EFI | POWERFUL WINCH 2500LBS
4X4 DUAL RANGE | DIFFERENTIAL LOCK
TOW HITCH | 6PLY TYRES

CROSSFIRE X600

ATV



The full-size Crossfire X600 comes equipped with a fuel injected 546cc engine and 4-wheel drive giving you the ability to tackle the toughest trails. The X600 is the most powerful quad in the Crossfire stable. The power for towing, the torque for working and a smooth effortless feel that will handle all terrain.

The Dual A-Arm nitrogen assisted shocks give the Crossfire 600 a smooth unforgettable ride. The X600's front and rear cargo racks and locale front differential and if all else fails a 2500LB Winch make it the right choice for your off-road adventure.

The fully automatic gear box with low range and high range transfer case are standard and electric power steering comes in handy in rough conditions acting as a damper against the bumps while providing assistance in the tight corners.

Equipped with a fuel injected 546cc engine and 4-wheel drive giving you the ability to tackle the toughest trails.

The minimum standard to pass the lateral stability tilt angle test is 28.81 degrees. The Crossfire X600 exceeds the minimum lateral stability tilt angle test with a result of 32.7 degrees.

With the introduction of the Quad bike safety standard, all Crossfire general use ATVs come standard with the Quad Bar Flexi inside every carton. Your dealer will fit this to the machine on pick up. It is mandatory for all our dealers to fit this CPD safety device in order to improve safety and comply with the Quad bike safety standard.

Engine	4-stroke SOHC
Displacement	546cc
Power	30 HP @6000rpm
Torque	40 N.m @5000rpm
Drive	2WD / 4WD Shaft
Cooling	Liquid
Carburettor	EFI
Starter	Electric
Ignition	ECU
Transmission	CVT L-H-N-R-P
Clutch	Wet multi-plate
Compression ratio	9.5:1
Bore x stroke	91 x 84 mm
Fuel capacity	17 L
Suspension front	Dual A-Arm, hydraulic w/ nitrogen assist
Suspension rear	Dual A-Arm, hydraulic w/ nitrogen assist
Wheelbase	1447 mm
Brakes front	Dual Disc
Brakes rear	Disc
Rims	12" steel
Tyres front	25 x 8-12
Tyres rear	25 x 10-12
Dimensions (L x W x H)	2286 x 1193 x 1384 mm
Seat height	930 mm
Ground clearance	279 mm
Empty vehicle weight (EVW)	390 kg
Max rider and cargo weight	288 kg
Towing capacity	544 kg inc rider
Winch	1100 kg
Cargo racks	Front & rear
Passenger backrest	Standard

AVAILABLE IN: 