

# CROSSFIRE AVENGER 700

## AVENGER 700

**INCREASED** GROUND CLEARANCE

**INDEPENDENT** FRONT AND REAR SUSPENSION

**ALUMINIUM** WHEELS | **2WD/4WD** WITH DIFFERENTIAL LOCK

**DRL** (DAY TIME RUNNING LIGHTS)

**WINCH** 2500 POUND | **ENGINE** BRAKING



# CROSSFIRE AVENGER 700

700cc ATV

## IMAGES



## DESCRIPTION

The Avenger is an ATV for someone who wants to have fun and play at the same time. With around 60Nm of Torque on hand the Avenger will work hard all day without working or needing to rev the engine to go.

*"..this 4wd ability is not simply for extremes but is about getting around even on the wet, muddy miserable days with ease and stability.."*

The bar work around the perimeter is standard; it is more rugged than plastic and in so provides years of durability. The front bar houses the 2500 Pound winch which is standard on the Avenger 700cc. On topic of durability – Crossfire Avenger 700 features independent all round suspension meaning better ground clearance and in so less damage to the undercarriage.

With selectable 4wd with Differential lock, the Avenger 700 is sure footed and will take you where you need to go. This 4wd ability is not simply for extremes but is about getting around even on the wet, muddy miserable days with ease and stability.

With standard winch, Day time Running Lights (DRL) and Aluminium wheels the 2015 Crossfire Avenger 700 is a rugged beauty.



## SPECIFICATIONS

Engine	LH1102U, One Cylinder, 4-Stroke, Water and Oil Cooling, SOHC
Bore x Stroke	85mm x 102mm
Compression Ratio	10.2:1
Max Torque and Rev	58Nm / 4500(r/min)
Max Power Output	30kw / 40.8HP
Displacement	695cc
Max Speed	95km/h
Start Type	Electric
Ignition Type	CDI
Transmission	CVT
Drive	Switchable 2WD/4WD with Differential lock
Suspension Front	McPherson independent suspension
Suspension Rear	Twin-A arm independent suspension
Shock Absorber	Spring Preloaded, Oil Damping
Braking	Hydraulic
Rims	Front: AT26X9-12, 100kPa Rear: AT26X10-12, 100kPa
Seat Height	925mm
Product Dimensions	2275mm x 1210mm x 1260 mm
Clearance	250mm
Wheelbase	1345mm
Minimum Turning Diameter	5000mm
Weight	382kg
Towing Capacity	200kg
Tank Capacity	16L
Payload Capacity	150kg

AVAILABLE IN:

