CROSSFIRE KANGA 90





CROSSFIRE KANGA 90



90cc ATV

IMAGES







DESCRIPTION

Crossfire Kanga generation 2 is the first major update in over 11 years for the Kanga range. It runs on regular unleaded without a need to mix oils. Its quiet and reliable with push button electric start.

Most importantly the new Kanga is lighter better engineered. This is achieved through a revolutionised Sigle A arm design which reduces parts making the new machine lighter and less complex to work on for the technicians. Also like all new Crossfires all lights on the Kanga are fully functional LED lights for both head and tail lights.

"...Most importantly the new Kanga is lighter and better engineered...."

The fully automatic transmission makes riding easy and more fun.

SPECIFICATIONS

Engine LC14FMD Clutch Type Wet multichip Measured Flow Capacity Rated Load Quality Carburetor PZ19 Compression Ratio Stroke Transmission Chain Transmission Ignition CDI Starter Electric Gearshift Fully Automatic Max Power / Relative Speed Single Rocker Independent Suspension Front Single Rocker Independent Suspension Rear Single Rocker Independent Suspension Shock Absorber Front: 270mm Rear: 250mm Front: Drum Brake Rear: Disc Brake Tyres / Wheels Front: 15*5.6-6, 600mm Seat Height 780mm Chassis Height 140mm Handle Height 780mm Minimum Turning Diameter Braking Manipulation (Front/Rear) Net Weight 69kg Minimum Ground Clearance Wheelbase 830±20mm Max Speed 60km/h Vehicle Size 1180 x 755 x 805 Battery 12V Fuel Grade 90# or above Fuel Capacity 2.5L Lubrication Oil Brand 15% and a company a		
Measured Flow Capacity Rated Load Quality88ml 45kgCarburetor Compression Ratio Cylinder Diameter x Stroke8.8:1Cylinder Diameter x Stroke47 x 41.4mmTransmission IgnitionChain Transmission CDIStarterElectricGearshift Max Power / Relative SpeedFully AutomaticMax Torque / Relative Speed5.6 N.m/5500 6000r/minSuspension FrontSingle Rocker Independent SuspensionSuspension RearSingle Rocker Independent SuspensionShock AbsorberFront: 270mm Rear: 250mmBrakesFront: Drum Brake Rear: Disc BrakeTyres / WheelsFront: 15*5.6-6, 600mmSeat Height140mmHandle Height780mmMinimum Turning Diameter2500±1200 mmBraking Manipulation (Front/Rear)Front and rear handbrakeNet Weight69kgMinimum Ground Clearance50mmWheelbase830±20mmMax Speed60km/hVehicle Size1180 x 755 x 805Battery12VFuel Grade90# or aboveFuel Capacity2.5LLubrication ModeLubrication 15W/40-SE(SUMMER) 10W/30-SF(WINTER) 10W/30-SF(WINTER) 11 Year Factory Doubles to 2 years if serviced at dealer ofWarrantyWarranty	Engine	LC14FMD
Rated Load Quality Carburetor Compression Ratio Cylinder Diameter x Stroke Transmission Ignition Starter Gearshift Max Power / Relative Speed Max Torque / Relative Speed Suspension Front Suspension Rear Single Rocker Independent Suspension Shock Absorber Brakes Front: Drum Brake Rear: Disc Brake Tyres / Wheels Seat Height Tandmum Turning Diameter Braking Manipulation (Front/Rear) Net Weight Max Speed Max Speed Momm Minimum Ground Clearance Wheelbase Battery 12V Fuel Grade Lubrication Oil Brand Univer At 14 Aum At 15 August Mixed Lubrication Oil Brand Liver At 14 Aum At 15 August Mixed Lubrication Doubles to 2 years if serviced at dealer of		•
Carburetor Compression Ratio Cylinder Diameter x Stroke Transmission Ignition CDI Starter Electric Gearshift Fully Automatic Max Power / Relative Speed Max Torque / Relative Speed Suspension Front Single Rocker Independent Suspension Suspension Rear Single Rocker Independent Suspension Shock Absorber Front: 270mm Rear: 250mm Front: 270mm Rear: 15*5.6-6, 600mm Rear: 15*5.6		
Cylinder Diameter x Stroke Transmission Ignition CDI Starter Electric Gearshift Max Power / Relative Speed Max Torque / Relative Speed Suspension Front Suspension Rear Single Rocker Independent Suspension Shock Absorber Brakes Front: 270mm Rear: 250mm Front: Drum Brake Rear: Disc Brake Tyres / Wheels Front: 15*5.6-6, 600mm Rear: 15*5.6-6, 600mm Seat Height T80mm Minimum Turning Diameter Braking Manipulation (Front and rear handbrake Rearing Manipulation (Front Rear) Rearing Manipulation (Front and rear handbrake Rearing Manipulation (Front and r		
Stroke Transmission Ignition Starter Gearshift Fully Automatic Max Power / Relative Speed Max Torque / Relative Speed Suspension Front Single Rocker Independent Suspension Suspension Rear Single Rocker Independent Suspension Shock Absorber Front: 270mm Rear: 250mm Front: 270mm Rear: 250mm Front: 15*5.6-6, 600mm Rear: 15*5.6-6, 600mm Rear: 15*5.6-6, 600mm Rear: 15*5.6-6, 600mm Rear: 15*5.6-6, 600mm Chassis Height Tomm Handle Height Tomm Minimum Turning Diameter Braking Manipulation (Front/Rear) Net Weight Geykg Minimum Ground Clearance Wheelbase Battery 12V Fuel Grade Fressure and Splash Mixed Lubrication Oil Brand 15W/40-SE(SUMMER) 10W/30-SE(SUMMER) 11 Year Factory Doubles to 2 years if serviced at dealer of		8.8:1
Ignition CDI Starter Electric Gearshift Fully Automatic Max Power / Relative Speed 5.6 N.m/5500 6000r/min Max Torque / Relative Speed Single Rocker Independent Suspension Front Single Rocker Independent Suspension Suspension Rear Single Rocker Independent Suspension Shock Absorber Front: 270mm Rear: 250mm Brakes Front: Drum Brake Rear: Disc Brake Tyres / Wheels Front: 15*5.6-6, 600mm Rear: 15*5.6-6, 600mm Chassis Height 140mm Handle Height 780mm Minimum Turning Diameter 2500±1200 mm Braking Manipulation (Front/Rear) Front and rear handbrake Met Weight 69kg Minimum Ground Clearance 50mm Max Speed 60km/h Vehicle Size 1180 x 755 x 805 Battery 12V Fuel Grade 90# or above Fuel Capacity 2.5L Lubrication Mode Lubrication Lubrication Oil Brand 15W/40-SE(SUMMER) 10W/30-SE(SUMMER) 10W/30-SE(SUMMER) 10W/30-SE(SUMMER) 11 Year Factory Doubles to 2 years if serviced at dealer of	Stroke	
Gearshift Max Power / Relative Speed A kW /8000r/min Max Torque / Relative Speed Suspension Front Single Rocker Independent Suspension Single Rocker Independent Suspension Single Rocker Independent Suspension Front: 270mm Rear: 250mm Brakes Front: Drum Brake Rear: Disc Brake Front: 15*5.6-6, 600mm Rear: 15*5.6-6, 600mm Seat Height Tyres / Wheels Seat Height T80mm Chassis Height T80mm Minimum Turning Diameter Braking Manipulation (Front/Rear) Net Weight 69kg Minimum Ground Clearance Wheelbase 830±20mm Max Speed 60km/h Vehicle Size 1180 x 755 x 805 Battery 12V Fuel Grade 90# or above Fuel Capacity 2.5L Lubrication Mode Lubrication Mode Lubrication Oil Brand 1 Year Factory Doubles to 2 years if serviced at dealer of		,
Max Power / Relative Speed Max Torque / Relative Speed Suspension Front Suspension Rear Suspension Rear Shock Absorber Brakes Front: 270mm Rear: 250mm Front: Drum Brake Rear: Disc Brake Front: 15*5.6-6, 600mm Rear: 15*5.6-6, 600mm Rear: 15*5.6-6, 600mm Seat Height Talomm Chassis Height Talomm Minimum Turning Diameter Braking Manipulation (Front/Rear) Net Weight 69kg Minimum Ground Clearance Wheelbase 830±20mm Max Speed 60km/h Vehicle Size 1180 x 755 x 805 Battery 12V Fuel Grade 90# or above Fuel Capacity 2.5L Lubrication Mode Lubrication Oil Brand 1 Year Factory Doubles to 2 years if serviced at dealer of	Starter	Electric
Speed Max Torque / Relative Speed Suspension Front Suspension Rear Suspension Rear Suspension Shock Absorber Brakes Front: 270mm Rear: 250mm Front: Drum Brake Rear: Disc Brake Front: 15*5.6-6, 600mm Rear: 15*5.6-6, 600mm Rear: 15*5.6-6, 600mm Rear: 15*5.6-6, 600mm Rear: 15*5.6-6, 600mm Seat Height Troma Chassis Height Taloma Minimum Turning Diameter Braking Manipulation (Front/Rear) Net Weight Geyg Minimum Ground Clearance Wheelbase 830±20mm Max Speed Gokm/h Vehicle Size 1180 x 755 x 805 Battery 12V Fuel Grade 90# or above Fuel Capacity 2.5L Lubrication Mode Lubrication Oil Brand 15W/40-SE(SUMMER) 10W/30-SF(WINTER) 1 Year Factory Doubles to 2 years if serviced at dealer of		Fully Automatic
Speed Suspension Front Single Rocker Independent Suspension Single Rocker Independent Suspension Front: 270mm Rear: 250mm Front: 270mm Rear: 250mm Brakes Front: Drum Brake Rear: Disc Brake Front: 15*5.6-6, 600mm Rear: 15*5.6-6, 600mm Front: 15*5.6-6,	Speed	4 kW /8000r/min
Suspension Suspension Rear Single Rocker Independent Suspension Front: 270mm Rear: 250mm Front: Drum Brake Rear: Disc Brake Tyres / Wheels Front: 15*5.6-6, 600mm Rear: 15*5.6-6, 600mm Chassis Height 780mm Minimum Turning Diameter Braking Manipulation (Front and rear handbrake Rear: Disc Brake Front: 15*5.6-6, 600mm Rear: 15*5.6-6, 600mm Front and rear handbrake Front and rear handbrake 69kg Minimum Ground Clearance Wheelbase 830±20mm Max Speed 60km/h Vehicle Size 1180 x 755 x 805 Battery 12V Fuel Grade 90# or above Fuel Capacity 2.5L Lubrication Mode Lubrication I5W/40-SE(SUMMER) 10W/30-SF(WINTER) 1 Year Factory Doubles to 2 years if serviced at dealer of	Conned	
Suspension Shock Absorber Brakes Front: 270mm Rear: 250mm Front: Drum Brake Rear: Disc Brake Front: 15*5.6-6, 600mm Rear: 15*5.6-6, 600mm Rear: 15*5.6-6, 600mm Rear: 15*5.6-6, 600mm Seat Height 570mm Chassis Height 140mm Handle Height 780mm Minimum Turning Diameter Braking Manipulation (Front/Rear) Net Weight 69kg Minimum Ground Clearance Wheelbase 830±20mm Max Speed 60km/h Vehicle Size 1180 x 755 x 805 Battery 12V Fuel Grade 90# or above Fuel Capacity 2.5L Lubrication Mode Lubrication Mode Lubrication Oil Brand 15W/40-SE(SUMMER) 10W/30-SF(WINTER) 1 Year Factory Doubles to 2 years if serviced at dealer of	Suspension Front	Suspension
Brakes Rear: 250mm Brakes Front: Drum Brake Rear: Disc Brake Tyres / Wheels Front: 15*5.6-6, 600mm Rear: 15*5.6-6, 600mm Seat Height 570mm Chassis Height 140mm Handle Height 780mm Minimum Turning Diameter 2500±1200 mm Braking Manipulation (Front/Rear) Front and rear handbrake Net Weight 69kg Minimum Ground Clearance 50mm Wheelbase 830±20mm Max Speed 60km/h Vehicle Size 1180 x 755 x 805 Battery 12V Fuel Grade 90# or above Fuel Capacity 2.5L Lubrication Mode Pressure and Splash Mixed Lubrication Lubrication Oil Brand 15W/40-SE(SUMMER) 10W/30-SF(WINTER) 1 Year Factory Doubles to 2 years if serviced at dealer of	Suspension Rear	Suspension
Brakes Front: Drum Brake Rear: Disc Brake Tyres / Wheels Front: 15*5.6-6, 600mm Rear: 15*5.6-6, 600mm Seat Height 570mm Chassis Height 140mm Handle Height 780mm Minimum Turning Diameter 2500±1200 mm Braking Manipulation (Front/Rear) Front and rear handbrake Net Weight 69kg Minimum Ground Clearance 50mm Wheelbase 830±20mm Max Speed 60km/h Vehicle Size 1180 x 755 x 805 Battery 12V Fuel Grade 90# or above Fuel Capacity 2.5L Lubrication Mode Pressure and Splash Mixed Lubrication Lubrication Oil Brand 15W/40-SE(SUMMER) 10W/30-SF(WINTER) 1 Year Factory Doubles to 2 years if serviced at dealer of	Shock Absorber	
Tyres / Wheels Front: 15*5.6-6, 600mm Rear: 15*5.6-6, 600mm Seat Height 570mm Chassis Height 140mm Handle Height 780mm Minimum Turning Diameter Braking Manipulation (Front/Rear) Net Weight 69kg Minimum Ground Clearance Wheelbase 830±20mm Max Speed 60km/h Vehicle Size 1180 x 755 x 805 Battery 12V Fuel Grade 90# or above Fuel Capacity 2.5L Lubrication Mode Lubrication Users and Splash Mixed Lubrication 15W/40-SE(SUMMER) 10W/30-SF(WINTER) 1 Year Factory Doubles to 2 years if serviced at dealer of	Dualina	•
Rear: 15*5.6-6, 600mm Seat Height 570mm Chassis Height 140mm Handle Height 780mm Minimum Turning Diameter 2500±1200 mm Braking Manipulation (Front and rear handbrake) Net Weight 69kg Minimum Ground Clearance 50mm Wheelbase 830±20mm Max Speed 60km/h Vehicle Size 1180 x 755 x 805 Battery 12V Fuel Grade 90# or above Fuel Capacity 2.5L Lubrication Mode Pressure and Splash Mixed Lubrication 15W/40-SE(SUMMER) 10W/30-SF(WINTER) 1 Year Factory Doubles to 2 years if serviced at dealer of	ытакез	
Chassis Height 140mm Handle Height 780mm Minimum Turning Diameter 2500±1200 mm Braking Manipulation (Front and rear handbrake) Net Weight 69kg Minimum Ground Clearance 50mm Wheelbase 830±20mm Max Speed 60km/h Vehicle Size 1180 x 755 x 805 Battery 12V Fuel Grade 90# or above Fuel Capacity 2.5L Lubrication Mode Pressure and Splash Mixed Lubrication 15W/40-SE(SUMMER) 10W/30-SF(WINTER) 1 Year Factory Doubles to 2 years if serviced at dealer of	Tyres / Wheels	
Handle Height 780mm Minimum Turning Diameter 2500±1200 mm Braking Manipulation (Front And rear handbrake) Net Weight 69kg Minimum Ground Clearance 50mm Wheelbase 830±20mm Max Speed 60km/h Vehicle Size 1180 x 755 x 805 Battery 12V Fuel Grade 90# or above Fuel Capacity 2.5L Lubrication Mode Pressure and Splash Mixed Lubrication Lubrication Oil Brand 15W/40-SE(SUMMER) 10W/30-SF(WINTER) 1 Year Factory Doubles to 2 years if serviced at dealer of	Seat Height	570mm
Minimum Turning Diameter Braking Manipulation (Front/Rear) Net Weight 69kg Minimum Ground Clearance 50mm Wheelbase 830±20mm Max Speed 60km/h Vehicle Size 1180 x 755 x 805 Battery 12V Fuel Grade 90# or above Fuel Capacity 2.5L Lubrication Mode Lubrication Oil Brand 15W/40-SE(SUMMER) 10W/30-SF(WINTER) 1 Year Factory Doubles to 2 years if serviced at dealer of	Chassis Height	140mm
Diameter Braking Manipulation (Front And rear handbrake) Net Weight 69kg Minimum Ground Clearance 50mm Wheelbase 830±20mm Max Speed 60km/h Vehicle Size 1180 x 755 x 805 Battery 12V Fuel Grade 90# or above Fuel Capacity 2.5L Lubrication Mode Pressure and Splash Mixed Lubrication 15W/40-SE(SUMMER) 10W/30-SF(WINTER) 1 Year Factory Doubles to 2 years if serviced at dealer of	Handle Height	780mm
Net Weight 69kg		2500±1200 mm
Minimum Ground Clearance Wheelbase 830±20mm Max Speed 60km/h Vehicle Size 1180 x 755 x 805 Battery 12V Fuel Grade 90# or above Fuel Capacity 2.5L Lubrication Mode Pressure and Splash Mixed Lubrication 15W/40-SE(SUMMER) 10W/30-SF(WINTER) 1 Year Factory Doubles to 2 years if serviced at dealer of		Front and rear handbrake
Clearance Wheelbase 830±20mm Max Speed 60km/h Vehicle Size 1180 x 755 x 805 Battery 12V Fuel Grade 90# or above Fuel Capacity 2.5L Lubrication Mode Pressure and Splash Mixed Lubrication 15W/40-SE(SUMMER) 10W/30-SF(WINTER) 1 Year Factory Doubles to 2 years if serviced at dealer of	Net Weight	69kg
Max Speed 60km/h Vehicle Size 1180 x 755 x 805 Battery 12V Fuel Grade 90# or above Fuel Capacity 2.5L Lubrication Mode Pressure and Splash Mixed Lubrication Lubrication Oil Brand 15W/40-SE(SUMMER) 10W/30-SF(WINTER) 1 Year Factory Doubles to 2 years if serviced at dealer of		50mm
Vehicle Size 1180 x 755 x 805 Battery 12V Fuel Grade 90# or above Fuel Capacity 2.5L Lubrication Mode Lubrication Oil Brand 15W/40-SE(SUMMER) 10W/30-SF(WINTER) 1 Year Factory Doubles to 2 years if serviced at dealer of	Wheelbase	830±20mm
Battery 12V Fuel Grade 90# or above Fuel Capacity 2.5L Lubrication Mode Pressure and Splash Mixed Lubrication Lubrication Oil Brand 15W/40-SE(SUMMER) 10W/30-SF(WINTER) 1 Year Factory Doubles to 2 years if serviced at dealer of	Max Speed	60km/h
Fuel Grade 90# or above Fuel Capacity 2.5L Lubrication Mode Lubrication Oil Brand 15W/40-SE(SUMMER) 10W/30-SF(WINTER) 1 Year Factory Doubles to 2 years if serviced at dealer of	Vehicle Size	1180 x 755 x 805
Fuel Capacity Lubrication Mode Lubrication Oil Brand Pressure and Splash Mixed Lubrication 15W/40-SE(SUMMER) 10W/30-SF(WINTER) 1 Year Factory Doubles to 2 years if serviced at dealer of	Battery	12V
Lubrication Mode Lubrication Oil Brand Lubrication Oil Brand Pressure and Splash Mixed Lubrication 15W/40-SE(SUMMER) 10W/30-SF(WINTER) 1 Year Factory Doubles to 2 years if serviced at dealer of	Fuel Grade	90# or above
Lubrication Mode Lubrication 15W/40-SE(SUMMER) 10W/30-SF(WINTER) 1 Year Factory Doubles to 2 years if serviced at dealer of	Fuel Capacity	
10W/30-SF(WINTER) 1 Year Factory Doubles to 2 years if serviced at dealer of	Lubrication Mode	Lubrication
Warranty years if serviced at dealer of	Lubrication Oil Brand	
	Warranty	years if serviced at dealer of

